

EXPO BEMAR WHITE



Proyector LED Blanco basado en 42 LEDS de 1w. Micrófono interno. Maestro / esclavo y programas internos. Conector: XLR 3 pin M / H. Powercon. Apertura: 30°. Lámpara: 42 LEDS x1w (18 cálidos + 24 fríos). Temperatura: 3200k - 5600k.

CalificaciónSin calificación

Precio

Modificador de variación de precio

Precio con descuento

Precio de venta con descuento:

Precio de venta: 479,16 €

Descuento

[Haga una pregunta del producto](#)

Fabricante:[BRITEQ](#)

Descripción

Características

- Very powerful white LED projector, based on 42 high power 1W LEDs (18 cool white + 24 warm white)
- The combination of cool and warm white LEDs makes it possible to change the color temperature of the light. (3200K – 5600K)
- Color temperature presets selectable via DMX
- Perfect alternative for traditional PAR64 projectors: only 50Watt power consumption + no need for heavy dimmer packs!
- The use of LED Technology makes important energy (cost) savings possible compared to units based on halogen lamps!
- This LED projector is your first choice to light up small, medium and large stages but also for shops, theaters and all kinds of other indoor venues.
- Different DMX operation modes:
 - 1 channel control (dim of custom preset)
 - 2 channel control (warm + cool white)
 - 2 channel control (dim + color temp. presets)

- 3 channel control (warm/cool white + dim)
 - 6 channel control (warm/cool white + dim + color temp. presets + strobe + ID-address)
- Thanks to all kinds of special features this projector is the choice of professional light designers:
 - Color temperature presets 3200K ~ 5600K
 - White Calibration
 - Different dimmer curves
 - ID-addressing
 - Neutrik PowerCon input/output (max. 24 units)
 - Neutrik 3pin DMX input/output
 - Menu driven LED-display with password protection on the rear panel
 - Tempered glass lens protection
- The 400Hz LED scan rate makes it also a perfect choice in TV studios (no interferences with TV-cameras)
- Completely silent: the projector is cooled by natural air convection so no noisy fans are needed!
- The lightweight aluminium housing uses a double hanging bracket so it can also be used as floor projector.
- Menu driven LED-display with password protection on the rear panel

Información Técnica

- Input voltage: 100 to 250Vac 50Hz/60Hz
- Power consumption: 50Wmax at full output
- Control protocol: DMX-512
- Dimmer: 0 – 100%
- Beam Angle: 30°
- Strobe speed: 0 – 20Hz
- Dimensions: 245 x 205 x 245mm
- Weight: 4,8kg

Comentario

No ha comentarios para este producto.